

(12) **United States Patent**
Perry

(10) **Patent No.:** **US 9,638,499 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **INSERT/OUTSERT ASSEMBLY FOR AN ARROW**

(71) Applicant: **Barnett Outdoors, LLC**, Tarpon Springs, FL (US)

(72) Inventor: **Dale Perry**, Goodyear, AZ (US)

(73) Assignee: **Barnett Outdoors, LLC**, Tarpon Springs, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,986,550 A *	1/1991	Segovia	F42B 6/08
				473/584
5,234,220 A *	8/1993	Schellhammer	F42B 6/04
				156/180
5,611,542 A	3/1997	Saunders		
7,004,859 B2	2/2006	Palomaki		
8,016,703 B1 *	9/2011	Kronengold	F42B 6/08
				473/582
8,475,303 B2 *	7/2013	James	F42B 6/08
				473/578
8,668,605 B1 *	3/2014	Huang	F42B 6/08
				473/582
2003/0159683 A1	8/2003	Muller		
2009/0163308 A1 *	6/2009	Odabachian	F42B 6/08
				473/582

(21) Appl. No.: **14/829,047**

(22) Filed: **Aug. 18, 2015**

(65) **Prior Publication Data**

US 2016/0054106 A1 Feb. 25, 2016

Related U.S. Application Data

(60) Provisional application No. 62/040,049, filed on Aug. 21, 2014.

(51) **Int. Cl.**
F42B 6/08 (2006.01)
F42B 6/04 (2006.01)

(52) **U.S. Cl.**
CPC . **F42B 6/04** (2013.01); **F42B 6/08** (2013.01)

(58) **Field of Classification Search**
CPC F42B 6/06; F42B 6/08
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,671,517 A * 6/1987 Winters F42B 6/08
403/165
4,874,180 A 10/1989 Fingerson

OTHER PUBLICATIONS

International Search Report and Written Opinion from Applicant's corresponding International Application No. PCT/US2015/045844, filed Aug. 19, 2015, titled "Insert/Outsert Assembly for an Arrow."

* cited by examiner

Primary Examiner — John Ricci

(74) *Attorney, Agent, or Firm* — Jones Walker LLP

(57) **ABSTRACT**

An insert/outsert assembly for an arrow. The insert includes a cylindrical body having first and second ends. The second end of the insert is dimensioned to fit within the bore of an arrow shaft. The first end includes a prong containing male threads. The outsert includes a cylindrical wall with an arrowshaft end and an arrowhead end. A center bore extends between the arrowshaft and arrowhead ends. The center bore contains a threaded region with female threads located intermediate of the arrowhead end and arrowshaft end. The insert is threadedly connected to the outsert. An arrowhead is threadedly connected to the outsert.

22 Claims, 4 Drawing Sheets

